



Hydraulic High-Pressure Accessories

(Version 04/2010)

bar	Manifold with adapters				Manifold with couplers			
	High-Pressure Hoses will be screwed on tightly				High-Pressure Hoses will be coupled			
700 - 1600								
	Art. No.	Connections	Pos. 4	Description	Art. No.	Connections	Pos. 4	Description
	B11540002	2	1	Manifold	B11550002	2	1	Manifold
			2	Quick-locking coupling nipple CVN16			2	Quick-locking coupling nipple CVN16
			3	Adapter G $\frac{1}{4}$ " AG / G $\frac{1}{4}$ " AG			3	Adapter G $\frac{1}{4}$ " AG / G $\frac{1}{4}$ " AG
B11540003	3	4	Adapter G $\frac{1}{4}$ " AG / M14x1,5 60° AG	B11550003	3	4	Quick-locking coupling sockets CVK16	
B11540004	4			B11550000...	optional as required			
B1154000...	optional as required			B1155000...	optional as required			
2500								
	Art. No.	Connections	Pos. 4	Description	Art. No.	Connections	Pos. 4	Description
	B11560002	2	1	Manifold	B11570002	2	1	Manifold
			2	Quick-locking coupling nipple CVN25-2			2	Quick-locking coupling nipple CVN25-2
			3	Adapter G $\frac{1}{4}$ " BSP 120° AG / G $\frac{1}{4}$ " BSP 120°			3	Adapter G $\frac{1}{4}$ " BSP 120° AG / G $\frac{1}{4}$ " BSP 120° AG
B11560003	3	4	Adapter G $\frac{1}{4}$ " BSP 120° AG / G $\frac{1}{4}$ " 60° AG	B11570003	3	4	Quick-locking coupling sockets CVK25-2	
B11560004	4			B11570000...	optional as required			
B1156000...	optional as required			B1157000...	optional as required			
3000 - 4000								
	Art. No.	Connections	Pos. 4	Description	Art. No.	Connections	Pos. 4	Description
	B11580002	2	1	Manifold	B11590002	2	1	Manifold
			2	Quick-locking coupling nipple SVN30			2	Quick-locking coupling nipple SVN30
			3	Adapter M16x1,5 58°DK / M16x1,5 58°DK			3	Adapter M16x1,5 58°DK / M16x1,5 58°DK
B11580003	3	4	Adapter M16x1,5 58° DK / G $\frac{1}{4}$ " 60° AG	B11590003	3	4	Quick-locking coupling sockets SVK30	
B1158000...	optional as required			B1159000...	optional as required			

All manifolds are manufactured according to customer's specification. This allows all options as required like separate shut-off per outlet, screwed on pressure gauges, round or square cross-section, pressure up to 4000 bar. The High-Pressure Hoses are manufactured appropriate to the pressure level and length as required.