



Hydraulic High-Pressure Hoses

up to 700 bar

Caution:
The high-pressure hose and all pressure-carrying parts associated with it, must always be inspected for damage before pressure is applied.
Damaged parts must immediately be replaced by new parts.

	A0567	A0568	A0569	A0649
Connection 1:	M14 x 1,5	CVN15	CVK15	M18 x 1,5
Connection 2:	M14 x 1,5	CVK15	M14 x 1,5	M18 x 1,5
Item 2:	--	Adapter G1/4" AG / M14 x 1,5 AG 60°		--
Item 3:	--	Quick-release coupling sleeve CVK15 G1/4" IG		--
Item 4:	--	Quick-release coupling nipple CVN15 G1/4" IG	--	--
Item 5:	--	--	--	--
Specialty:	--	Items 3 and 4 are dimensioned for a max. operating pressure of 1000 bar.	Item 3 is dimensioned for a max. operating pressure of 1000 bar	--
Max. operating pres. for item 1:	700 bar			
Test pressure for item 1:	1400 bar			
Bursting pressure for item 1:	2800 bar			
Inner tube:	Polyamide			
Pressure jacket:	2 spiralled layers of high tensile steel wire			
Outer sheath:	Black PUR			
Inside-Ø:	6.3 mm			
Outside-Ø:	13.3 mm			
Outside -Ø incl. protect. hose:	22.0 mm			
Weight:	0.27 kg/m			
Minimum bending radius:	70 mm			
Max. cycles-to-failure count:	10,000			
Ambient temperature:	-40 °C to +100 °C			

Other lengths are available at short notice upon request, as these are assembled by SCHAAF.
All items are available individually.

www.schaaf-gmbh.com

Visit us on the internet and convince yourself of our innovative services and products.

SCHAAF has been developing and manufacturing high-pressure hydraulic tools since 1954.

