

HDL 1000-4000

Air-Hydraulic Pump Rugged - Efficient - Safe



Leading joining technology






HDL 1000-2500 / 1600-4000

Air-Hydraulic Pumps ready for immediate use at hydraulic pressures of 2500 to 4000 bar.

Air pressure connection and maintenance unit with air oiler, pressure relief valve Distributor block for individual selection of number and type of pressure connections, optionally also with secondary pressure limitation valve.

Foot valve for remote operation

Primary circuit pressure relief valve to prevent damage.



High-capacity pressure intensifier with safety valves for optimum and uniform pressure build-up to meet even the highest requirements.

Transmission ratios:

- 1 bar air pressure

 425 bar hydraulic pressure
- 1 bar air pressure ≜ 740 bar hydraulic pressure

Large aluminium tank with 6-litre oil volume.



Primary circuit safety valve to prevent damage.

Rugged design for workshops and construction sites.

Areas of Application

The SCHAAF HDL Series is ideally suited for:

- The use of bolt tensioners, hydraulic nuts, ExpaTen Bolts and EcoRolls
- Tightening and loosening of oil press fits (e.g., gearwheels, flywheels, coupling hubs, roller bearings, hydraulic couplings and overload protection devices)

Type code and additional information under **www.schaaf-gmbh.com**



Advantages

The SCHAAF **HDL Series** is a high-capacity, compact air-hydraulic high-pressure unit, specially designed for industrial use.

- Rugged, compact and durable design
- Small dimensions
- Low weight
- Immediately ready for use, fully assembled and oil filled
- All components sealed leakproof
- No pressure loss even at 4000 bar
- Manufactured in high-quality materials
- Hardened, replaceable valve seats
- Pressure relief valve with internal tank return line
- Permanently installed in mobile housing
- Low-maintenance operation
- Distributor block for up to four connections

Any special version possible

Complete solution from SCHAAF

The accessories for the **HDL Series** such as hydraulic hoses, connection couplings, as well as the hydraulic high-pressure tools such as bolt tensioners and hydraulic nuts are aligned to the functions = 100 % system solution.

SCHAAF Accessories and additional product groups

- High-pressure hydraulic hoses
- Couplings, nipples, adapters and distributor blocks for pressures up to 4,000 bar
- Bolt Tensioners (SSV)
- TTG Nuts and Bolts
- ShrinkNut
- Hydraulic Nuts (HM)
- GripLoc, GripLoc MSN
- ExpaTen Bolts, ExpaHub, ExpaTen QL

Certificates and Acceptance Tests

- Specific test reports
- Certificates as per special customer requirements

Quality Assurance

All **HDL** 1000-4000 are checked for material quality, dimensional accuracy, correct functioning and load-resistance. During order execution, they are subject to continuous quality assurance measures and are supplied together with detailed technical documentation.

Services

HDL 1000-4000 are, of course, oil filled and ready for immediate use.

SCHAAF HDL 1000-4000 are user-friendly, reliable, and manufactured in accordance with the highest level of technical know-how. Our highly-motivated staff would be pleased to train your personnel, in situ or at our works, in the general handling and operation of high-pressure equipment.



SCHAAF GmbH & Co. KG

Bruesseler Allee 22 41812 Erkelenz - Germany

Telephone: +49 - 24 31 - 9 77 70 - 0 Fax: +49 - 24 31 - 9 77 70-77

E-Mail: info@schaaf-gmbh.com Internet: www.schaaf-gmbh.com

